
OM50 Ultrasonic Homogenizer (50W)



homogenizer that will occupy less bench space than any unit on the market.

This model is effective for standard cell disruption and many other small volume applications. Probes are available in three different sizes.



Stand sold separately.

Technical specifications Specify desired voltage when ordering		
Power rating	50 Watts	
Frequency	20 kHz	
Dimensions	W: 8" (20.0 cm), D: 7.5" (19.0 cm), H: 5.75" (14.6 cm)	
Voltage	110 or 220V 50/60 Hz	

OM50 Includes power supply, convertor, cables and wrench set

Features

- Smallest unit available
- Thumb-switch or continuous operation
- Simple and effective operation
 - Power on/off switch
 - Amplitude control
 - Continuous or thumb switch-activated processing



OM50 accessories

Probes

Probe part #	Processing volume	Tip diameter	Amplitude
060-078	200 μL to 5 mL	5/64" (1.6 mm)	200 μm
060-125	500 μL to 15 mL	1/8" (3.2 mm)	180 μm
060-250	5 mL to 50 mL	1/4" (6.4 mm)	120 μm





Sound enclosure with converter holder W: 12" (30.5 cm), D: 12" (30.5 cm), H: 20" (50.8 cm) (Part number: 060-12)



Replacement converter (Part number: 060-03)



Support stand with converter holder (Part number: 060-10)



